

Threaded pipe fittings

**20 bar à 20°C**
16 bar à 100°C**ACCESSOIRES
DE TUYAUTERIE**Modèle **5224****Traversée de cloison - Inox 316L**

Bulkhead coupling - Stainless steel 316L

Gaz cylindrique

DN (mm)	DN (pouces)	F1 (pouces)	F2 (pouces)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence Gaz cylindrique	Prix unitaire
8	1/4"	1/2"	1/4"	35	8	8	18	30	27	0,09	652244-8	70,70
10	3/8"	1/2"	3/8"	35	8	8	18	30	27	0,10	652244-10	74,40
15	1/2"	3/4"	1/2"	40	9	10	20	36	32	0,13	652244-15	86,60
20	3/4"	1"	3/4"	40	10	11	20	46	38	0,21	652244-20	114,40
25	1"	1 1/4"	1"	45	11	13	22	55	50	0,35	652244-25	141,60
32	1 1/4"	1 1/2"	1 1/4"	50	12	13	22	60	60	0,42	652244-32	170,50
40	1 1/2"	2"	1 1/2"	54	12	14	26	75	70	0,78	652244-40	209,00
50	2"	2 1/2"	2"	58	14	16	26	95	90	1,62	652244-50	•
65	2 1/2"	3"	2 1/2"	66	14	19	31	105	105	1,95	652244-65	•
80	3"	4"	3"	72	14	22	32	124	124	3,42	652244-80	•
100	4"	5"	4"	75	14	23	36	155	150	4,74	652244-100	•

Filetages selon la norme ISO 228-1

• Sur demande