

Threaded pipe fittings




20 bar à 20°C

16 bar à 100°C

Modèle **5228**

## Bouchon mâle conique à tête carrée - ISO 4144 - Inox 316 moulé

Square head male plug (casting) - Stainless steel 316



| DN<br>(mm) | DN<br>(pouces) | F<br>(pouces) | L1<br>(mm) | L2<br>(mm) | S<br>(mm) | Poids<br>(kg) | Référence<br>Gaz conique | Prix<br>unitaire | Référence<br>NPT | Prix<br>unitaire |
|------------|----------------|---------------|------------|------------|-----------|---------------|--------------------------|------------------|------------------|------------------|
| 6          | 1/8"           | 1/8"          | 17         | 12         | 7         | 0,01          | 452283-6                 | 2,50             | 452285-6         | •                |
| 8          | 1/4"           | 1/4"          | 20         | 12         | 9         | 0,02          | 452283-8                 | 2,90             | 452285-8         | •                |
| 10         | 3/8"           | 3/8"          | 22         | 13         | 11        | 0,03          | 452283-10                | 4,20             | 452285-10        | •                |
| 15         | 1/2"           | 1/2"          | 25         | 15         | 13        | 0,05          | 452283-15                | 5,10             | 452285-15        | •                |
| 20         | 3/4"           | 3/4"          | 27         | 17         | 16        | 0,08          | 452283-20                | 6,80             | 452285-20        | •                |
| 25         | 1"             | 1"            | 32         | 20         | 20        | 0,16          | 452283-25                | 8,10             | 452285-25        | •                |
| 32         | 1"1/4          | 1"1/4         | 35         | 21         | 24        | 0,30          | 452283-32                | 13,70            | 452285-32        | •                |
| 40         | 1"1/2          | 1"1/2         | 36         | 22         | 25        | 0,42          | 452283-40                | 23,10            | 452285-40        | •                |
| 50         | 2"             | 2"            | 38         | 24         | 32        | 0,62          | 452283-50                | 27,30            | 452285-50        | •                |

Filetage selon la norme ISO 7/1

• Sur demande