

Threaded pipe fittings


ISO 7/1
(sauf NPT)


20 bar à 20°C
16 bar à 100°C
ACCESSOIRES
DE TUYAUTERIEModèle **5239****Réduction femelle / femelle - Inox 316L usiné**

Female / female reducer - Stainless steel 316L



DN (mm)	F1 (pouces)	F2 (pouces)	L1 (mm)	L2 (mm)	S (mm)	Poids (kg)	Référence Gaz cylindrique	Prix unitaire	Référence NPT	Prix unitaire
8-6	1/4"	1/8"	23	13	17	0,03	652394-86	5,80	652395-86	11,10
10-6	3/8"	1/8"	26	14	23	0,07	652394-106	8,70		
10-8	3/8"	1/4"	26	14	23	0,06	652394-108	9,20	652395-108	11,90
15-6	1/2"	1/8"	26	16	24	0,06	652394-156	10,40		
15-8	1/2"	1/4"	28	16	24	0,07	652394-158	10,40	652395-158	12,40
15-10	1/2"	3/8"	28	16	24	0,05	652394-1510	10,40	652395-1510	13,50
20-6	3/4"	1/8"	28	16	30	0,13	652394-206	•		
20-8	3/4"	1/4"	28	16	30	0,11	652394-208	14,40	652395-208	•
20-10	3/4"	3/8"	28	16	30	0,10	652394-2010	14,40		
20-15	3/4"	1/2"	28	16	30	0,09	652394-2015	14,40	652395-2015	15,80
25-8	1"	1/4"	31	19	38	0,19	652394-258	19,70		
25-10	1"	3/8"	31	19	38	0,18	652394-2510	19,70		
25-15	1"	1/2"	31	19	38	0,17	652394-2515	19,70		
25-20	1"	3/4"	33	19	38	0,17	652394-2520	19,70	652395-2520	32,80
32-10	1"1/4	3/8"	32	20	50	0,34	652394-3210	35,10		
32-15	1"1/4	1/2"	33	20	50	0,34	652394-3215	35,10		
32-20	1"1/4	3/4"	34	20	50	0,34	652394-3220	35,10		
32-25	1"1/4	1"	39	20	50	0,36	652394-3225	35,10		
40-15	1"1/2	1/2"	35	21	55	0,43	652394-4015	45,40		
40-20	1"1/2	3/4"	35	21	55	0,41	652394-4020	45,40		
40-25	1"1/2	1"	39	21	55	0,48	652394-4025	45,40		
40-32	1"1/2	1"1/4	40	21	55	0,39	652394-4032	48,20		
50-20	2"	3/4"	40	23	65	0,63	652394-5020	68,40		
50-25	2"	1"	40	23	65	0,60	652394-5025	66,00		
50-32	2"	1"1/4	42	23	65	0,57	652394-5032	64,80		
50-40	2"	1"1/2	42	23	65	0,51	652394-5040	54,00		
65-25	2"1/2	1"	55	35	83	1,33	652394-6525	•		
65-32	2"1/2	1"1/4	60	35	83	1,45	652394-6532	•		
65-40	2"1/2	1"1/2	60	35	83	1,37	652394-6540	•		
65-50	2"1/2	2"	60	35	83	1,19	652394-6550	131,00		
80-50	3"	2"	70	40	96	2,00	652394-8050	•		
80-65	3"	2"1/2	70	40	96	1,64	652394-8065	•		

• Sur demande