


Hose fittings

ACCESSOIRES  
DE TUYAUTERIE

Modèle **5275**

## Raccord tournant avec roulement à billes mâle / femelle - Inox 316

Male / female bearing swivel union - Stainless steel 316



| Désignation     | D<br>(mm) | F1<br>(pouces) | F2<br>(pouces) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | S1<br>(mm) | S2<br>(mm) | Poids<br>(kg) | Référence<br>Gaz cylindrique | Prix<br>unitaire |
|-----------------|-----------|----------------|----------------|------------|------------|------------|------------|------------|---------------|------------------------------|------------------|
| 1/2" M x 1/2" F | 9         | 1/2"           | 1/2"           | 40         | 15         | 11         | 27         | 27         | 0,12          | <b>452751-1515</b>           | •                |
| 1/2" M x 3/4" F | 9         | 1/2"           | 3/4"           | 40         | 15         | 10         | 27         | 30         | 0,12          | <b>452752-1520</b>           | •                |
| 1/2" M x 3/4" F | 14        | 1/2"           | 3/4"           | 50         | 15         | 15         | 30         | 30         | 0,14          | <b>452753-1520</b>           | •                |
| 3/4" M x 3/4" F | 12        | 3/4"           | 3/4"           | 40         | 15         | 10         | 30         | 30         | 0,14          | <b>452754-2020</b>           | •                |
| 1" M x 1" F     | 18        | 1"             | 1"             | 48         | 18         | 13         | 36         | 36         | 0,22          | <b>452755-2525</b>           | •                |

Joint NBR - 30 bar max - 85°C max

Filetages selon la norme ISO 228-1

• Sur demande