

Raccords à simple bague


Série
54RACCORDS
À BAGUE

Single cutting ring fittings

**DIN 2353****ISO 7/1** (sauf NPT)Modèle **5416**

Union simple femelle - DIN 2353 - Inox 316 Ti

Female straight union - DIN 2353 - Stainless steel 316 Ti



Série	PN (bar)	D (mm)	F (pouces)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence BSPP	Prix unitaire	Référence NPT	Prix unitaire
L	315	6	1/8"	34	19	14	14	0,03	454163-66	23,00	454165-66	34,50
L	315	6	1/4"	39	24	14	19	0,04	454163-68	25,10	454165-68	34,50
L	315	8	1/4"	39	24	17	19	0,05	454163-88	28,60	454165-88	35,90
L	315	10	1/4"	40	25	19	19	0,05	454163-108	28,60	454165-108	37,00
L	315	12	3/8"	41	26	22	24	0,07	454163-1210	35,40	454165-1210	45,20
L	315	12	1/2"	46	30	22	27	0,11	454163-1215	38,40	454165-1215	47,40
L	315	15	3/8"	42	27	27	24	0,10	454163-1510	41,20	454165-1510	•
L	315	15	1/2"	46	31	27	27	0,11	454163-1515	43,20	454165-1515	61,60
L	315	18	3/8"	44	28	32	27	0,14	454163-1810	56,90	454165-1810	64,30
L	315	18	1/2"	47	31	32	27	0,16	454163-1815	53,00	454165-1815	73,40
S	630	14	1/2"	50	32	27	27	0,16	454163-1415	52,30	454165-1415	•
S	400	16	1/2"	50	31	30	30	0,16	454163-1615	53,60	454165-1615	91,80
S	400	20	3/4"	56	34,5	36	36	0,25	454163-2020	80,40	454165-2020	141,20
S	400	25	1"	62	38	46	41	0,48	454163-2525	110,20	454165-2525	272,00
S	400	30	1"1/4	69	43	50	55	0,62	454163-3032	189,30	454165-3032	•
S	250	38	1"1/2	74	44	60	60	0,89	454163-3840	229,00	454165-3840	•

Autres diamètres sur demande

• Sur demande