

Single cutting ring fittings




DIN 2353

Modèle **5421**

Union double de réduction - DIN 2353 - Inox 316 Ti

Reducer union - DIN 2353 - Stainless steel 316 Ti



Série	PN (bar)	D1 (mm)	D2 (mm)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	S3 (mm)	Poids (kg)	Référence	Prix unitaire
LL	100	6	4	32,5	10,5	12	11	10	0,02	454217-64	27,60
L	315	8	6	40	11	17	14	14	0,04	454217-86	28,10
L	315	10	6	41	12	19	17	14	0,05	454217-106	30,60
L	315	10	8	41	12	19	17	17	0,06	454217-108	32,20
L	315	12	8	42	13	22	19	17	0,07	454217-128	32,40
L	315	12	10	43	14	22	19	19	0,08	454217-1210	35,50
L	315	15	10	44,5	15	27	24	19	0,11	454217-1510	44,70
L	315	15	12	44,5	15	27	24	22	0,12	454217-1512	42,30
L	315	18	12	46	15,5	32	27	22	0,16	454217-1812	60,40
L	315	18	15	47,5	16,5	32	27	27	0,18	454217-1815	85,90
L	400	14	10	54	20	27	24	22	0,20	454217-1410	62,10
L	400	14	12	54	20	27	24	24	0,20	454217-1412	60,00
L	400	16	12	54	20	30	27	24	0,22	454217-1612	63,20
L	400	20	16	62,5	23	36	32	30	0,30	454217-2016	100,20
L	400	25	16	68	25,5	46	41	30	0,53	454217-2516	154,70
L	400	25	20	71	25,5	46	41	36	0,55	454217-2520	162,70
S	400	30	20	73	27	50	46	36	0,60	454217-3020	216,40
S	400	30	25	77	27	50	46	46	0,62	454217-3025	224,30
S	315	38	25	82	29	60	55	46	0,67	454217-3825	328,50
S	315	38	30	95	29	60	55	50	0,70	454217-3830	328,50

Autres diamètres sur demande