


Single cutting ring fittings



DIN 2353

Modèle **5430****Coude orientable avec bague pré-sertie - DIN 2353 - Inox 316 Ti**

Orientable elbow union - DIN 2353 - Stainless steel 316 Ti



Série	PN (bar)	D (mm)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	S3 (mm)	Poids (kg)	Référence	Prix unitaire
L	315	6	27	12	14	12	14	0,04	454307-6	39,20
L	315	8	29	14	17	12	17	0,05	454307-8	40,50
L	315	10	30	15	19	14	19	0,07	454307-10	49,30
L	315	12	32	17	22	17	22	0,09	454307-12	56,10
L	315	15	36	21	27	19	27	0,15	454307-15	83,20
L	315	18	40	23,5	32	24	32	0,23	454307-18	101,60
S	630	14	40	22	27	19	27	0,19	454307-14	86,20
S	400	16	43	24,5	30	24	30	0,24	454307-16	102,90
S	400	20	48	26,5	36	27	36	0,37	454307-20	156,90
S	400	25	54	30	46	36	46	0,73	454307-25	223,50
S	400	30	62	35,5	50	41	50	0,97	454307-30	320,70
S	315	38	72	41	60	50	60	1,39	454307-38	480,00

Autres diamètres sur demande