

Cam locking couplings



U.S. MIL-C-27487 /

A-A-59326A




de -0,8 à +16 bar

de -20°C à +65°C

RACCORDS
RAPIDESModèle **5526****Coupleur filetage Gaz conique type B à cames sécurisées - Joint NBR
Inox 316**

BSPT threaded male coupler with safety locking cams - NBR gasket - Stainless steel 316



DN (mm)	DN (pouces)	D1 (mm)	D2 (mm)	F (pouces)	L (mm)	Poids (kg)	Référence Inox 316	Prix unitaire
20	3/4"	32,4	19	3/4"	56	0,20	455263-20	•
25	1"	37,3	24,5	1"	65	0,49	455263-25	•
32	1"1/4	46	33	1"1/4	74	0,48	455263-32	•
40	1"1/2	54	39	1"1/2	74	0,51	455263-40	•
50	2"	63,8	50	2"	81	0,70	455263-50	•
65	2"1/2	76,5	63	2"1/2	90	0,94	455263-65	•
80	3"	92,2	77,5	3"	94	1,60	455263-80	•
100	4"	120,3	101	4"	103	2,15	455263-100	•

Pression de service : de -0,8 à +16 bar

• Sur demande

Température de service : de -20°C à +65°C

Filetage selon la norme ISO 7/1