

SMS unions




CE 1935/2004

NORME SMS

Modèle **61115****Joint de raccord en L**

Gasket for union (L section)

EPDMModèle **61386****FKM (BNIC)**Modèle **61387****PTFE**Modèle **61390****Silicone**

DN (mm)	DN (pouces)	D1 (mm)	D2 (mm)	D3 (mm)	Référence EPDM	Prix unitaire	Référence FKM	Prix unitaire
25	1"	32	25	22,5	961115-25	1,20	961386-25	5,70
38	1 1/2"	48	38	35,5	961115-38	1,30	961386-38	7,00
51	2"	61	51	48,5	961115-51	1,70	961386-51	9,30
63	2 1/2"	73,5	63,5	60,5	961115-63	2,60	961386-63	15,20
76	3"	86	76	72,9	961115-76	2,70	961386-76	16,70
104	4"	116	104	100	961115-104	3,60	961386-104	23,80

DN (mm)	DN (pouces)	D1 (mm)	D2 (mm)	D3 (mm)	Référence PTFE	Prix unitaire	Référence Silicone	Prix unitaire
25	1"	32	25	22,5	961387-25	11,40	961390-25	3,70
38	1 1/2"	48	38	35,5	961387-38	19,60	961390-38	5,20
51	2"	61	51	48,5	961387-51	22,90	961390-51	5,70
63	2 1/2"	73,5	63,5	60,5	961387-63	29,10	961390-63	6,20
76	3"	86	76	72,9	961387-76	34,20	961390-76	7,40
104	4"	116	104	100	961387-104	66,00	961390-104	10,20

Température (EPDM) : -40°C à +135°C (150°C en pointe)

Température (FKM) : -15°C à +220°C

Température (PTFE) : -100°C à +200°C

Température (Silicone) : -40°C à +160°C