

DIN unions



CE 1935/2004

NORME DIN

Modèle **62394**



Joint de raccord semi-torique

Gasket for union (half-tore section)

NBR



Modèle **62395**

FKM (BNIC)



Modèle **62396**

PTFE




Modèle **62397**

EPDM



Modèle **62398**

Silicone



DN (mm)	D1 (mm)	D2 (mm)	L (mm)	Référence NBR	Prix unitaire	Référence FKM	Prix unitaire	Référence PTFE	Prix unitaire
10	20	12	4,5	962394-10	1,00	962395-10	9,70	962396-10	17,90
15	26	18	4,5	962394-15	1,00	962395-15	9,70	962396-15	17,90
20	33	23	4,5	962394-20	1,20	962395-20	9,70	962396-20	17,90
25	40	30	5	962394-25	1,20	962395-25	11,40	962396-25	17,90
32	46	36	5	962394-32	1,40	962395-32	12,40	962396-32	17,90
40	52	42	5	962394-40	1,80	962395-40	14,40	962396-40	17,90
50	64	54	5	962394-50	1,90	962395-50	17,10	962396-50	17,90
65	81	71	5	962394-65	2,10	962395-65	25,10	962396-65	27,50
80	95	85	5	962394-80	3,20	962395-80	26,90	962396-80	29,40
100	114	104	6	962394-100	3,30	962395-100	32,80	962396-100	32,10
125	142	130	7	962394-125	5,90	962395-125	55,90	962396-125	70,70
150	167	155	7	962394-150	11,70	962395-150	61,10	962396-150	71,60

DN (mm)	D1 (mm)	D2 (mm)	L (mm)	Référence EPDM	Prix unitaire	Référence Silicone	Prix unitaire
10	20	12	4,5	962397-10	1,90	962398-10	2,80
15	26	18	4,5	962397-15	1,90	962398-15	1,90
20	33	23	4,5	962397-20	1,90	962398-20	2,80
25	40	30	5	962397-25	1,40	962398-25	12,50
32	46	36	5	962397-32	1,40	962398-32	12,50
40	52	42	5	962397-40	1,40	962398-40	12,50
50	64	54	5	962397-50	2,00	962398-50	12,50
65	81	71	5	962397-65	3,30	962398-65	14,80
80	95	85	5	962397-80	3,30	962398-80	24,00
100	114	104	6	962397-100	3,70	962398-100	43,40
125	142	130	7	962397-125	7,40	962398-125	12,90
150	167	155	7	962397-150	11,70	962398-150	17,40

Température (NBR) : -30°C à +100°C

Température (FKM) : -15°C à +220°C

Température (PTFE) : -100°C à +200°C

Température (EPDM) : -40°C à +135°C (150°C en pointe)

Température (Silicone) : -40°C à +160°C