

MACON unions



CE 1935/2004

MACON

Modèle **64116****Joint de raccord**

Gasket for union

**NR SBR**Modèle **64117****FKM (BNIC)**

| DN<br>(mm) | D1<br>(mm) | D2<br>(mm) | E<br>(mm) | Référence<br>NR SBR | Prix<br>unitaire | Référence<br>FKM  | Prix<br>unitaire |
|------------|------------|------------|-----------|---------------------|------------------|-------------------|------------------|
| 40         | 49         | 42,5       | 3         | <b>964116-40</b>    | 1,30             | <b>964117-40</b>  | •                |
| 50         | 61         | 52,5       | 3         | <b>964116-50</b>    | 1,70             | <b>964117-50</b>  | •                |
| 60         | 72         | 62,5       | 3         | <b>964116-60</b>    | 2,30             | <b>964117-60</b>  | •                |
| 70         | 84         | 72,5       | 3         | <b>964116-70</b>    | 3,30             | <b>964117-70</b>  | •                |
| 80         | 98         | 82,5       | 3         | <b>964116-80</b>    | 4,00             | <b>964117-80</b>  | •                |
| 100        | 118        | 102,5      | 3         | <b>964116-100</b>   | 4,40             | <b>964117-100</b> | •                |

Température (NR SBR) : -30°C à +70°C

• Sur demande

Température (FKM) : -15°C à +220°C

