


ECROU HEXAGONAL AUTOFREINE A RONDELLE CONTACT STRIEE TWOLOCK® CS

Modèle
78601

ACIER ZN RENFORCE 400 HBS



RÉFÉRENCES MEMENTO TECHNIQUE

7.9 Choix d'un revêtement conforme ROHS
4.6 Les écrous



TWOLOCK® CS HEXAGON NUT WITH
CONTACT LOCK WASHER ALCALIN ZINC
PLATED 400 HSST

TUERCA HEXAGONAL AUTOBLOQUANTE A
ARANDELA CONTACT ESTRIADA TWOLOCK®
CS ACERO ZINCADO BLANCO ALCALIN
400 HBS

DADO ESAGONALE AUTOFRENANTE AD
ROSETTA «CONTACT» ZIGRINATA TWOLOCK
® CS ACCIAIO ZINCATO ALCALINO 400 ORE
NS



VIS A TÊTE
HEXAGONALE
ENTIEREMENT
FILETÉE
Modèle 20211
Page A 09



VIS A TÊTE
HEXAGONALE
PARTIELLEMENT
FILETÉE
Modèle 20011
Page A 19

d nominal	M4	M5	M6	M8	M10	M12
Pas (mm)	0,7	0,8	1	1,25	1,5	1,75
a max. (mm)	7	8	10	13	16	18
h min. (mm)	2,9	4,4	4,9	6,44	8,04	10,37
d ₂ max. (mm)	10,2	12,2	14,2	18,2	22,25	27,25
H max. (mm)	4,6	5,7	6,9	8,98	11,05	13,75

Référence	d (mm)
786014	4
786015	5

Référence	d (mm)
786016	6
786018	8

Référence	d (mm)
7860110	10
7860112	12